

MINOR SOURCE OPERATING PERMIT OFFICE OF AIR MANAGEMENT

**F Systems, Inc.
111 N. Industrial Drive
Lynn, Indiana 47355**

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages. This permit and the conditions listed herein replace and supercede Registered Source Status - Construction, issued pursuant to Sections 2 and 3 of Regulation APC 19 on August 22, 1979.

Operation Permit No.: MSOP 135-10861-00031	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

TABLE OF CONTENTS

A	SOURCE SUMMARY	4
A.1	General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]	
A.2	Emission Units and Pollution Control Equipment Summary	
B	GENERAL CONSTRUCTION CONDITIONS	5
B.1	Permit No Defense [IC 13]	
B.2	Definitions	
B.3	Effective Date of the Permit [IC 13-15-5-3]	
B.4	Revocation of Permits [326 IAC 2-1.1-9(5)]	
B.5	Modification to Permit [326 IAC 2]	
B.6	Minor Source Operating Permit [326 IAC 2-6.1]	
C	SOURCE OPERATION CONDITIONS	7
C.1	PSD Minor Source Status [326 IAC 2-2]	
C.2	Preventive Maintenance Plan [326 IAC 1-6-3]	
C.3	Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]	
C.4	Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)]	
C.5	Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]	
C.6	Permit Revocation [326 IAC 2-1-9]	
C.7	Opacity [326 IAC 5-1]	
C.8	Fugitive Dust Emissions [326 IAC 6-4]	
C.9	Stack Height [326 IAC 1-7]	
C.10	Performance Testing [326 IAC 3-6]	
C.11	Compliance Monitoring [326 IAC 2-1.1-11]	
C.12	Maintenance of Monitoring Equipment [IC 13-14-1-13]	
C.13	Monitoring Methods [326 IAC 3]	
C.14	Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 1-6]	
C.15	Actions Related to Noncompliance Demonstrated by a Stack Test	
	Record Keeping and Reporting Requirements	
C.16	Malfunctions Report [326 IAC 1-6-2]	
C.17	Monitoring Data Availability [326 IAC 2-6.1-2] [IC 13-14-1-3]	
C.18	General Record Keeping Requirements [326 IAC 2-6.1-2]	
C.19	General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]	
D.1	Emissions unit OPERATION CONDITIONS - Two (2) Paint Booths	16
	Emission Limitations and Standards	
D.1.1	Volatile Organic Compounds (VOC) [326 IAC 8-2-9]	
D.1.2	Particulate Matter (PM) [326 IAC 6-3-2(c)]	
D.1.3	Preventive Maintenance Plan [326 IAC 1-6-3]	
	Compliance Determination Requirements	
D.1.4	Testing Requirements	
D.1.5	Volatile Organic Compounds (VOC)	
	Compliance Monitoring Requirements	
D.1.6	Particulate Matter (PM)	
D.1.7	Monitoring	

Record Keeping and Reporting Requirements

D.1.8 Record Keeping Requirements

D.1.9 Reporting Requirements

Malfunction Report	19
---------------------------	-----------

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM). The information describing the source contained in conditions A.1 through A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary surface coating source that paints metal truck axles.

Authorized Individual: Renee Thrashed
Source Address: 111 N. Industrial Drive, Lynn, Indiana 47355
Mailing Address: 111 N. Industrial Drive, Lynn, Indiana 47355
Phone Number: 765-874-2531
SIC Code: 3559
County Location: Randolph
County Status: Attainment for all criteria pollutants
Source Status: Minor Source Operating Permit
Minor Source, under PSD Rules

A.2 Emissions units and Pollution Control Equipment Summary

This stationary source is approved to construct and operate the following emissions units and pollution control devices:

- (a) One (1) spray paint booth identified as Paint Booth #1, coating a maximum of twenty-two (22) truck axles per hour, equipped with a high volume-low pressure (HVLP) spray application system and dry filter particulate matter overspray control system, exhausting at one (1) stack identified as PB1; and
- (b) One (1) spray paint booth identified as Paint Booth #2, coating a maximum of forty-five (45) truck axles per hour, equipped with a high volume-low pressure (HVLP) spray application system and double dry filter particulate matter overspray control system, exhausting at two (2) stacks identified as PB2 and PB3.

SECTION B GENERAL CONSTRUCTION CONDITIONS

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1.1 AND 40 CFR 52.780, WITH CONDITIONS LISTED BELOW.

B.1 Permit No Defense [IC 13]

This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2, and 326 IAC 2-1.1-1 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this permit becomes effective upon its issuance.

B.4 Revocation of Permits [326 IAC 2-1.1-9(5)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this permit if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

B.5 Modification to Permit [326 IAC 2]

All requirements and conditions of this construction permit shall remain in effect unless modified in a manner consistent with procedures established for modifications of construction permits pursuant to 326 IAC 2 (Permit Review Rules).

B.6 Minor Source Operating Permit [326 IAC 2-6.1]

This document shall also become a minor source operating permit pursuant to 326 IAC 2-6.1 when, prior to start of operation, the following requirements are met:

- (a) The attached affidavit of construction shall be submitted to the Office of Air Management (OAM), Permit Administration & Development Section, verifying that the emissions units were constructed as proposed in the application. The emissions units covered in the this Minor Source Operating Permit may begin operating on the date the affidavit of construction is postmarked or hand delivered to IDEM.
- (b) If construction is completed in phases; i.e., the entire construction is not done continuously, a separate affidavit must be submitted for each phase of construction. Any permit conditions associated with operation start up dates such as stack testing for New Source Performance Standards (NSPS) shall be applicable to each individual phase.
- (c) The Permittee shall receive an Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section and attach it to this document.
- (d) The operation permit will be subject to annual operating permit fees pursuant to 326 IAC 2-1.1-7(Fees).
- (e) Pursuant to 326 IAC 2-6.1-7, the Permittee shall apply for an operation permit renewal at least ninety (90) days prior to the expiration date established in the validation letter. If IDEM, OAM, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied. The operation permit issued shall contain as a minimum the conditions in Section C and Section D of this permit.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

C.1 Minor Source Status [326 IAC 2-7] [326 IAC 2-2] [40 CFR 52.21]

- (a) The total source potential to emit of any regulated pollutant, including volatile organic compounds (VOC), any individual hazardous air pollutant (HAP), and total HAPs, are respectively less than 100 tons per year, 10 tons per year, and 25 tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Permit Program), and the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) and 40 CFR 52.21, do not apply.

- (b) Any change or modification which may respectively increase potential to emit any regulated pollutant, individual HAP, or total HAPs to 100 tons per year, 10 tons per year or 25 tons per year from this source, shall cause this source to be considered a major source under Part 70, 326 IAC 2-7, and shall require approval from IDEM, OAM prior to making the change.
- (c) Any change or modification which may increase potential to emit any regulated pollutant to 250 tons per year from this source, shall cause this source to be considered a major source under PSD, 326 IAC 2-2 and 40 CFR 52.21, and shall require approval from IDEM, OAM prior to making the change.

C.2 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this permit, including the following information on each emissions unit:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM.

C.3 Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]

- (a) The Permittee must comply with the requirements of [326 IAC 2-6.1-6] whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1.

- (c) The Permittee shall notify the OAM within thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]

C.4 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, the Permittee shall allow IDEM, OAM, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under this title or the conditions of this permit or any operating permit revisions;
- (c) Inspect, at reasonable times, any processes, emissions units (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit or any operating permit revisions;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.
 - (1) The Permittee may assert a claim that, in the opinion of the Permittee, information removed or about to be removed from the source by IDEM, OAM, or an authorized representative, contains information that is confidential under IC 5-14-3-4(a). The claim shall be made in writing before or at the time the information is removed from the source. In the event that a claim of confidentiality is so asserted, neither IDEM, OAM, nor an authorized representative, may disclose the information unless and until IDEM, OAM, makes a determination under 326 IAC 17-1-7 through 326 IAC 17-1-9 that the information is not entitled to confidential treatment and that determination becomes final. [IC 5-14-3-4; IC 13-14-11-3; 326 IAC 17-1-7 through 326 IAC 17-1-9]
 - (2) The Permittee and IDEM, OAM, acknowledge that the federal law applies to claims of confidentiality made by the Permittee with regard to information removed or about to be removed from the source by U.S. EPA. [40 CFR Part 2, Subpart B]

C.5 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]

Pursuant to [326 IAC 2-6.1-6(d)(3)]:

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAM, Permits Branch within thirty (30) days of the change.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an notice-only change pursuant to 326 IAC 2-6.1-6(d)(3).
- (c) IDEM, OAM, shall issue a revised permit.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

C.6 Permit Revocation [326 IAC 2-1-9]

Pursuant to 326 IAC 2-1-9(a)(Revocation of Permits), this permit to construct and operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.7 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

C.8 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.9 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted by using ambient air quality modeling pursuant to 326 IAC 1-7-4.

Testing Requirements

C.10 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing methods approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

Compliance Monitoring Requirements

C.11 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this permit. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend the compliance schedule an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date. The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

C.12 Maintenance of Monitoring Equipment [IC 13-14-1-13]

- (a) In the event that a breakdown of the monitoring equipment occurs, a record shall be made of the times and reasons of the breakdown and efforts made to correct the problem. To the extent practicable, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less frequent than required in Section D of this permit until such time as the monitoring equipment is back in operation. In the case of continuous monitoring, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less than one (1) hour until such time as the continuous monitor is back in operation.

- (b) The Permittee shall install, calibrate, quality assure, maintain, and operate all necessary monitors and related equipment. In addition, prompt corrective action shall be initiated whenever indicated.

C.13 Monitoring Methods [326 IAC 3]

Any monitoring or testing performed to meet the applicable requirements of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

C.14 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 1-6]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
 - (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this permit;
 - (3) The Compliance Monitoring Requirements in Section D of this permit;
 - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
 - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of :
 - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and
 - (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
 - (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.

- (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

C.15 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected emissions unit while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate permit conditions may be grounds for immediate revocation of the permit to operate the affected emissions unit.

The documents submitted pursuant to this condition do not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

Record Keeping and Reporting Requirements

C.16 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM) or appointed representative upon request.

- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAM, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.17 Monitoring Data Availability [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) With the exception of performance tests conducted in accordance with Section C-Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.18 General Record Keeping Requirements [326 IAC 2-6.1-2]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAM, representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

- (b) Records of required monitoring information shall include, where applicable:
 - (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
 - (1) Copies of all reports required by this permit;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.19 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) To affirm that the source has met all the compliance monitoring requirements stated in this permit the source shall submit a Semi-annual Compliance Monitoring Report. Any deviation from the requirements and the date(s) of each deviation must be reported. The Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.

- (d) Unless otherwise specified in this permit, any semi-annual report shall be submitted within thirty (30) days of the end of the reporting period. The report does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) All instances of deviations must be clearly identified in such reports. A reportable deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:
 - (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
 - (2) A malfunction as described in 326 IAC 1-6-2; or
 - (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
 - (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred or failure to monitor or record the required compliance monitoring is a deviation.
- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

SECTION D.1

EMISSIONS UNIT OPERATION CONDITIONS

Emissions unit Description:

- (a) One (1) spray paint booth identified as Paint Booth #1, coating a maximum of twenty-two (22) truck axles per hour, equipped with a high volume-low pressure (HVLP) spray application system and dry filter particulate matter overspray control system, exhausting at one (1) stack identified as PB1; and
- (b) One (1) spray paint booth identified as Paint Booth #2, coating a maximum of forty-five (45) truck axles per hour, equipped with a high volume-low pressure (HVLP) spray application system and double dry filter particulate matter overspray control system, exhausting at two (2) stacks identified as PB2 and PB3.

Emission Limitations and Standards

D.1.1 Volatile Organic Compound (VOC) [326 IAC 8-2-9]

Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coating delivered to the applicators of the two (2) paint booths (Paint Booth #1 and Paint Booth #2) shall be limited to 3.5 pounds of VOCs per gallon of coating less water, for air dried coating.

Solvent sprayed from application equipment during cleanup or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

D.1.2 Particulate Matter (PM) [326 IAC 6-3-2(c)]

The PM from the two (2) paint booths (Paint Booth #1 and Paint Booth #2) shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

or

Interpolation and extrapolation of the data for the process weight rate in excess of sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 55.0 P^{0.11} - 40$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

D.1.3 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these emission units and their control devices.

Compliance Determination Requirements

D.1.4 Testing Requirements [326 IAC 2-1.1-11]

The Permittee is not required to test these emission units by this permit. However, IDEM may require compliance testing when necessary to determine if the emissions unit is in compliance. If testing is required by IDEM, compliance with the volatile organic compound (VOC) limit specified in Condition D.1.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

D.1.5 Volatile Organic Compounds (VOC)

Compliance with the VOC content limitation contained in Condition D.1.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. IDEM, OAM, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.6 Particulate Matter (PM)

The dry filters for PM control shall be in operation at all times when the two (2) paint booths (Paint Booth #1 and Paint Booth #2) are in operation.

D.1.7 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks (PB1, PB2, and PB3) while the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.

- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.8 Record Keeping Requirements

- (a) To document compliance with Condition D.1.1, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limit(s) and/or the VOC emission limit(s) established in Condition D.1.1.
- (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
- (2) A log of the dates of use;
- (3) The cleanup solvent usage for each month, exclusive of acetone solvent usage;
- (4) The total VOC usage for each month; and
- (5) The weight of VOCs emitted for each month.
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.9 Reporting Requirements

There are no specific reporting requirements for this facility.

MALFUNCTION REPORT

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR MANAGEMENT FAX NUMBER - 317 233-5967

**This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6
and to qualify for the exemption under 326 IAC 1-6-4.**

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?____, 25 TONS/YEAR SULFUR DIOXIDE ?____, 25 TONS/YEAR NITROGEN OXIDES?____, 25 TONS/YEAR VOC ?____, 25 TONS/YEAR HYDROGEN SULFIDE ?____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?____, 25 TONS/YEAR FLUORIDES ?____, 100TONS/YEAR CARBON MONOXIDE ?____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF 'MALFUNCTION' AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY: F Systems, Inc. PHONE NO. (765) 874 - 2531
LOCATION: (CITY AND COUNTY) Lynn, Randolph County
PERMIT NO. MSOP 135-10861-00031 AFS PLANT ID: 00031 AFS POINT ID: 01 INSP: Warren Greiling
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON: _____

DATE/TIME MALFUNCTION STARTED: ____/____/ 19____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION:

DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE ____/____/ 19____ AM/PM

TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO2, VOC, OTHER: _____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____

MEASURES TAKEN TO MINIMIZE EMISSIONS: _____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: _____

CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: _____

CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: _____

INTERIM CONTROL MEASURES: (IF APPLICABLE) _____

MALFUNCTION REPORTED BY: _____ TITLE: _____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY: _____ DATE: _____ TIME: _____

*SEE PAGE 2

**Please note - This form should only be used to report malfunctions
applicable to Rule 326 IAC 1-6 and to qualify for
the exemption under 326 IAC 1-6-4.**

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

***Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

Indiana Department of Environmental Management Office of Air Management

Technical Support Document (TSD) for a Minor Source Operating Permit

Source Background and Description

Source Name: F Systems, Inc.
Source Location: 111 N. Industrial Drive, Lynn, Indiana 47355
County: Randolph
SIC Code: 3559
Operation Permit No.: MSOP 135-10861-00031
Permit Reviewer: Michael Hirtler / EVP

The Office of Air Management (OAM) has reviewed an application from F Systems, Inc. relating to the construction and operation of a new spray paint booth and increased production at the existing spray paint booth. The proposed modification is subject to 326 IAC 2-6.1 and, therefore, the source will be issued a first-time Minor Source Operating Permit (MSOP).

New Emission Units and Pollution Control Equipment

The application includes information relating to the construction and operation of the following equipment:

- (a) One (1) spray paint booth identified as Paint Booth #1, coating a maximum of twenty-two (22) truck axles per hour, equipped with a high volume-low pressure (HVLP) spray application system and dry filter particulate matter overspray control system, exhausting at one (1) stack identified as PB1; and
- (b) One (1) spray paint booth identified as Paint Booth #2, coating a maximum of forty-five (45) truck axles per hour, equipped with a high volume-low pressure (HVLP) spray application system and double dry filter particulate matter overspray control system, exhausting at two (2) stacks identified as PB2 and PB3.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted facilities operating at this source during this review process.

Existing Approvals

The source has been operating under previous approvals including, but not limited to, the following:

- (a) Registered Source Status - Construction (no registration number), issued on August 22, 1979.

This proposed permit, MSOP 135-10861-00031, and the conditions contained herein, supercede and replace the Registered Source Status - Construction, issued on August 22, 1979, and all conditions contained therein.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
PB1	spray painting	30	2.833	18,750	68
PB2	spray painting	34	2.833	16,000	68
PB3	spray painting	34	2.833	16,000	68

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the construction and operation be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

A complete application for the purposes of this review was received on April 12, 1999.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (two (2) pages).

Potential To Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source or emissions unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA, the department, or the appropriate local air pollution control agency.”

Pollutant	Potential To Emit (tons/year)
PM	87.1
PM-10	87.1
SO ₂	0.0
VOC	94.88
CO	0.0
NO _x	0.0

HAP's	Potential To Emit (tons/year)
xylene	1.6
cumene	0.7
cobalt compounds	0.4
TOTAL	2.7

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of volatile organic compounds (VOC), particulate matter (PM) and particulate matter with an aerodynamic diameter at or below 10 microns (PM-10) are each equal to or greater than 25 tons per year. Therefore, as an existing source and pursuant to 326 IAC 2-6.1, a minor source operating permit is required for construction and operation associated with this source modification.

(b) Fugitive Emissions

Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are not counted toward determination of PSD and Emission Offset applicability.

County Attainment Status

The source is located in Randolph County.

Pollutant	Status
PM-10	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NO_x) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Randolph County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.
- (b) Randolph County has been classified as attainment or unclassifiable for all remaining criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

Source Status

Existing Source PSD Definition (emissions after controls, based on 8,760 hours of operation per year at rated capacity and/ or as otherwise limited):

Pollutant	Emissions (ton/yr)
PM	0.4
PM10	0.4
SO ₂	0
VOC	24.1
CO	0
NO _x	0

- (a) This existing source is not a major stationary source because no attainment regulated pollutant is emitted at a rate of 250 tons per year or more, and it is not in one of the 28 listed source categories.
- (b) These emissions were based on the source modification application submitted by the company.

Proposed Modification

PTE from the proposed modification (based on 8,760 hours of operation per year at rated capacity including enforceable emission control and production limits, where applicable):

Pollutant	PM (ton/yr)	PM10 (ton/yr)	SO ₂ (ton/yr)	VOC (ton/yr)	CO (ton/yr)	NO _x (ton/yr)
Proposed Modification	1.2*	1.2*	0.0	94.9*	0.0	0.0
PSD or Offset Threshold Level	250	250	250	250	250	250

** This proposed source modification will supercede the existing registered status for this source. As such, and for purposes of future permit review, the emissions presented in this table are for the entire source and will replace the "Existing Source PSD Definition" emissions of the previous section.*

This modification to an existing minor stationary source is not major because the emission increase is less than the PSD significant emission threshold levels. Therefore, pursuant to 326 IAC 2-2, and 40 CFR 52.21, the PSD requirements do not apply.

Part 70 Permit Determination

326 IAC 2-7 (Part 70 Permit Program)

This existing source, including the emissions from this permit MSOP 135-10861-00031, is still not subject to the Part 70 Permit requirements because the potential to emit (PTE) of:

- (a) each criteria pollutant is less than 100 tons per year,
- (b) a single hazardous air pollutant (HAP) is less than 10 tons per year, and
- (c) any combination of HAPs is less than 25 tons/year.

This status is based on all the air approvals issued to the source. This status has been verified by the OAM inspector assigned to the source.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 61) applicable to this source.
- (c) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 20 and 40 CFR Part 63) applicable to this source.

State Rule Applicability - Entire Source

326 IAC 1-6-3 (Preventive Maintenance Plan)

The source shall prepare and maintain a Preventive Maintenance Plan (PMP) for the surface coating facilities and their control devices within ninety (90) days after issuance of this approval. Current OAM policy requires that a PMP be prepared pursuant to the requirements of 326 IAC 1-6-3 (Preventive Maintenance Plan) for surface coating facilities and related control devices.

326 IAC 2-4.1-1 (New Source Toxics Control)

Pursuant to 326 IAC 2-4.1-1 (New Source Toxics Control), any new process or production unit, which in and of itself emits or has the potential to emit (PTE) 10 tons per year of any HAP or 25 tons per year of all HAPs combined, and is constructed or reconstructed after July 27, 1997, must be controlled using technologies consistent with Maximum Achievable Control Technology (MACT). Paint Booth #1 is an existing source installed in 1979. Paint Booth #2 is a new process unit to be constructed after the July 27, 1997 rule applicability date; however, it does not result in a PTE single or total HAPs in excess of the respective thresholds. Therefore, the requirements of this rule do not apply to this source.

326 IAC 2-6 (Emission Reporting)

This source is located in Randolph County, it is not one of the twenty-eight (28) listed sources, and its potential to emit VOC and PM10 is less than one-hundred (100) tons per year for each pollutant, including fugitive emissions, therefore, 326 IAC 2-6 does not apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

326 IAC 6-4 (Fugitive Dust Emissions)

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

State Rule Applicability - Individual Facilities

326 IAC 8-2-9 (Miscellaneous Metal Coating Operations)

Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coating delivered to the applicators of the two (2) paint booths (Paint Booth #1 and Paint Booth #2) shall be limited to 3.5 pounds of VOCs per gallon of coating less water, for air dried coating.

Solvent sprayed from application equipment during cleanup or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

Based on the MSDS submitted by the source and calculations made, the paint booths are in compliance with this requirement.

326 IAC 6-3-2 (Process Operations)

Pursuant to 326 IAC 6-3-2, the PM from the two (2) paint booths (Paint Booth #1 and Paint Booth #2) shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

or

Interpolation and extrapolation of the data for the process weight rate in excess of sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 55.0 P^{0.11} - 40 \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

The dry filter PM control systems for the two (2) paint booths (Paint Booth #1 and Paint Booth #2) shall be in operation at all times that the facilities are in operation, in order to comply with this limit.

Air Toxic Emissions

Indiana presently requests applicants to provide information on emissions of the 188 hazardous air pollutants (HAPs) set out in the Clean Air Act Amendments of 1990. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries. They are listed as air toxics on the Office of Air Management (OAM) Construction Permit Application Form Y.

- (a) This source will emit levels of air toxics less than those which constitute a major source according to Section 112 of the 1990 Clean Air Act Amendments.
- (b) See attached calculations for detailed air toxic calculations (page 2 of 2 in Appendix A).

Conclusion

The construction and operation of this source modification, including a new spray paint booth and increased production at the existing spray paint booth, shall be subject to the conditions of the attached proposed **Minor Source Operating Permit 135-10861-00031**.

**Appendix A: Emission Calculations
VOC and Particulate
From Surface Coating Operations**

Company Name: F Systems, Inc.
Address City IN Zip: 111 N. Industrial Drive, Lynn, Indiana 47355
Permit No.: MSOP 135-10861-00031
Reviewer: Michael Hirtler / EVP
Date: April 21, 1999

Potential Uncontrolled Emissions:																		
Coating Material (as applied)	Product Being Coated	Density (Lb/Gal)	Weight % Volatile (H20& Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Vol (solids)	Gal of Mat (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential ton/yr	lb VOC /gal solids	Transfer Efficiency	
Paint Spray Booth 1																		
Black Primer	Metal Truck Axles	11.71	27.61%	0.00%	27.61%	0.00%	52.91%	0.1	22	3.23	3.23	7.11	170.71	31.15	28.59	6.11	65%	
Paint Spray Booth 2																		
Black Primer	Metal Truck Axles	11.71	27.61%	0.00%	27.61%	0.00%	52.91%	0.1	45	3.23	3.23	14.55	349.18	63.73	58.48	6.11	65%	
Total Uncontrolled Potential to Emit:												21.66	519.89	94.88	87.07			
Total Controlled Potential to Emit:									VOC Input Usage Limitation	Booth 1 Control Efficiency	Booth 2 Control Efficiency	Controlled VOC lbs per Hour	Controlled VOC lbs per Day	Controlled VOC tons per Year	Controlled PM tons/yr			
									VOC	PM	PM							
									0.00%	98.00%	99.00%	21.66	519.89	94.88	1.16			

Methodology:
Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)
Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)
Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)
Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)
Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)
Potential Particulate Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) * (8760 hrs/yr) * (1 ton/2000 lbs)
Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids) * Transfer Efficiency
Total Uncontrolled Potential VOC Emissions = Sum of Worst Case Coatings Applied + Sum of all Solvents Used (Note: the solvent used at this source is acetone which is not reactive photochemically and it is not considered as a VOC)
Total Uncontrolled Potential Particulate Emissions = Sum of Worst Case Coatings Applied
Controlled VOC Emission Rate = Uncontrolled Emission Rate * (1 - VOC Input Limitation)
Controlled PM Emission Rate = ((Booth 1 Uncontrolled Emission Rate * (1 - Control Efficiency)))+(Booth 2 Uncontrolled Emission Rate * (1-Control Efficiency)) * (1- VOC Input Limitation)

Page 2 of 2, TSD AppA

[illegible]